

What are the BNWAS requirements?

BNWAS Regulations

IMO - Solas Chapter V Regulation 19

The requirements making it mandatory to have a <u>bridge navigational watch alarm system (BNWAS)</u> fitted to all passenger and cargo vessels can be found in the amendments made to <u>SOLAS Chapter V Regulation</u> <u>19</u> that were adopted by the IMO on 5th June 2009 in Resolution MSC.282(86).

The changes see the following subparagraph is added to paragraph 2.2 of the regulations:

- .3 a bridge navigational watch alarm system (BNWAS), as follows:
- .1 cargo ships of 150 gross tonnage and upwards and passenger ships irrespective of size constructed on or after 1 July 2011;
- .2 passenger ships irrespective of size constructed before 1 July 2011, not later than the first survey* after 1 July 2012;
- .3 cargo ships of 3,000 gross tonnage and upwards constructed before 1 July 2011, not later than the first survey* after 1 July 2012;
- .4 cargo ships of 500 gross tonnage and upwards but less than 3,000 gross tonnage constructed before 1 July 2011, not later than the first survey* after 1 July 2013; and
- .5 cargo ships of 150 gross tonnage and upwards but less than 500 gross tonnage constructed before 1 July 2011, not later than the first survey* after 1 July 2014.

The bridge navigational watch alarm system shall be in operation whenever the ship is underway at sea;

.4 a bridge navigational watch alarm system (BNWAS) installed prior to 1 July 2011 may subsequently be exempted from full compliance with the standards adopted by the Organization, at the discretion of the Administration."

BNWAS Compliance Dates

BNWAS Implementation Schedule - July 2011 to July 2014

